



ACP-2300

*Overlock stitch conveyor curtain
sewing machine*



Matériel industriel & Fournitures pour le Textile & le Cuir
2 avenue de La Tessoualle - BP71212
49312 CHOLET CEDEX FRANCE

Accueil 02 41 65 85 32 / contact@maugin-sas.com
Pièces détachées 02 41 65 08 08 / www.maugin-parts.com



1.



2.



3.



watch the video

1. Pegasus 4- or 5 thread EXT series
2. Optional: Double zippy edge guide
3. Fabric clamp

- Equipped with Pegasus high-speed 2-needle, 4 or 5 thread safety stitch machine with variable top and bottom driven roller featuring a minimum lubrication system to prevent oil stains at the needle bar.
- Combined top transport and bottom roller. And featuring a minimum lubrication system to prevent oil stains at the needle bar.
- Advanced pneumatic controlled single zippy guide for problem free pattern matching when joining panels with even selvages.
- Sewing unit is electrically removable to ease threading, cleaning and maintenance.
- Start/stop drawstrings placed over the full length of the frame provide an important contribution to the efficiency of the machine and the ergonomics for the operator.
- Compact, space-saving frame, equipped with a synchronised conveyor belt with a length of 550 cm.
- Simple and user-friendly operation.
- Optional: Electro hydraulic height adjustment for ergonomic work positions.
- Optional: Advanced pneumatic controlled double zippy independent guides for problem free pattern matching when joining panels with uneven selvages.
- Production capacity: 60-75 panels per hour (average panel length 250 cm)*.
- Technical specifications:
 - Dimensions: 550 x 160 cm
 - Electric: 220 V, 1 phase, 1350 W, 16 A
 - Air: 6 bar, 0,5 L per cycle

* capacity strongly dependent on the operator.